



C



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

GB04/4325

REC'D 17 NOV 2004

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)


Signed

Andrew Gersey

Dated

9 November 2004

BEST AVAILABLE COPY



Patents Form 1/77

Patents Act 1977
(Rule 16)28OCT03 E847725-1 002813
P01/7700 0.00-0325078.4

1777

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

THE PATENT OFFICE
JR
28 OCT 2003
RECEIVED BY FAX

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

1.	Your Reference	P59067F-GB		
2.	Patent Application number (The Patent Office will fill in this part)	0325078.4		
3.	Full name, address and postcode of the or each applicant (underline all surnames)	BAHORUN, Lee Dunbar 70 Balcombe Road Horley Surrey RH6 9AY 873 7009001		
	Patents ADP Number (if you know it)			
	If the applicant is a corporate body, give the country/state of its incorporation			
4.	Title of the invention	A FIRE EXTINGUISHER		
5.	Name of your agent (if you have one)	FRY HEATH & SPENCE LLP		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	The Gables Massetts Road Horley Surrey RH6 7DQ United Kingdom 8459554001		
	Patents ADP Number (if you know it)	05880270004		
6.	Priority: Complete this section if you are declaring priority from one or more earlier patent applications filed in the last 12 months.	Country	Priority application number (if you know it)	Date of filing (day / month / year)
		GB	0324508.1	21.10.2003
7.	Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f).	Number of earlier application	Date of filing (day / month / year)	
8.	Is a Patents Form 1/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?	No		

Patents Form 1/77

0084038 28 Oct 03 11:44

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Continuation sheets of this form 0

Description 7

Claim(s) 0

Abstract 0

Drawing(s) 2

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 0

Request for preliminary examination and search (Patents form 9/77) 0

Request for substantive examination (Patents form 10/77) 0

Any other documents (please specify) 0

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

Fry Heath & Spence LLP.

28 October 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

David J. Fry - 01293 776880

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you filing or applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under sections 8(3), 12(6) and 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should complete part 6 with the priority details.

A FIRE EXTINGUISHER

The present invention relates to a fire extinguisher.

Fires continue to destroy the possessions and lives of everyday people. The majority of buildings, including private homes, contain one or more fire extinguishers for use in an emergency to prevent spread of fire, at least until the fire service can be contacted and arrive to control and stop the fire. Fire extinguishers contain various materials, for example, water, carbon dioxide, powder or halon to combat fires of different types. The different materials contained within each fire extinguisher cylinder are generally characterised by a prominent colour on the fire extinguisher.

Fire extinguishers, by law, should be kept in a prominent place near to each fire exit of the building. They need to be easily accessible to anyone should they need to use the fire extinguisher in an emergency.

Through his own experience, the present applicant has discovered an important problem with fire extinguishers currently available and being used, to which this application is addressed.

The particular problem with fire extinguishers on the market relates to the ability to locate the fire extinguisher in the event of a fire. Although every person in the building should be aware of the location of the fire extinguisher on a day-to-day basis, thick smoke produced by a fire prevents the location to be found easily and quickly. Moreover, the ensuing panic of a person not trained in fire situations, commonly results in severe disorientation to the extent that the person is unable to work out where they are in the building in relation to the fire extinguisher.

Furthermore, even when the fire extinguisher is located, the pin of the fire extinguisher often cannot be easily located due to the extreme

visibility problems caused by the thick smoke. In such a situation, it is usually the case that everything, including the fire extinguisher cylinder, the pin and indeed the hands of the person trying to use the extinguisher, are quickly covered in a dense black residue. Consequently, specific parts of extinguisher are not easy to find in a few seconds. Vital seconds, and even minutes are therefore lost in trying to activate the fire extinguisher, at least to help in being able to reach the fire exit, or contain the fire until help arrives.

The present invention seeks to alleviate the problem described above by providing a fire extinguisher which has a visual or oral indicator to allow the location fire extinguisher to be easily assessed in an emergency situation. Furthermore, as, by law, fire extinguishers must be located in the vicinity of a fire exit of a building, locating the position of the fire extinguishers will also aid the location of the fire exit.

According to one aspect, there is provided a fire extinguisher comprising a cylindrical body, a handle and a pin, the extinguisher having at least one indicating device mounted thereon to provide a clear indication as to the location of the fire extinguisher.

Preferably, the indicating device provides a visual indication of the location of the fire extinguisher. Alternatively the indication device comprises an audio indication, or a combination of visual and audio indication.

Preferably, the, or at least one indication device is an LED. Preferably still, the or each LED provides a colour that corresponds with a representative colour of the material contained within the extinguisher cylinder.

Preferably still the or one indication device is mounted on, or in the immediate vicinity of, the pin. Preferably still, an indication device is mounted either side of the pin.

In a preferred embodiment, at least one indication device is mounted on a side surface of the extinguisher, preferably near the base thereof. The or each indication device is an LED that is preferably in a position whereupon light is transmitted from the LED to a person in the vicinity of the extinguisher without obstruction.

Preferably, the or each indication device is an LED mounted on a strip.

Preferably still, the strip includes means to power the or each LED. The strip also, preferably, includes means to attach the strip to a fire extinguisher. Preferably, the attachment means takes the form of a suitable adhesive, alternatively the attachment means may take the form of a male/female linking mechanism.

According to a second aspect, there is provided a stand for a fire extinguisher the stand having a surface not obstructed by the fire extinguisher located on the stand in use, the surface having at least one indicating device mounted thereon to provide a clear indication as to the location of the fire extinguisher stand.

The invention will now be described by way of example with reference to the accompanying diagrammatic drawings, in which :-

Figure 1 is a side view of a fire extinguisher constructed in accordance with the present invention;

Figure 2 is a side view of a further embodiment of a fire extinguisher constructed in accordance with the present invention;

Figure 3 is a side view of a handle and pin of the fire extinguisher of Figure 1 or 2;

Figure 4 is a view from the other side of the handle and pin of the fire extinguisher of Figure 3;

Figure 5 is a plan view of an indicating device constructed in accordance with the present invention; and

Figure 6 is a side view of a stand constructed in accordance with the present invention.

Referring first to Figure 1, a fire extinguisher comprises a cylinder 10, a handle 12 and a pin 14. The handle 12 comprises two arms 16 which provide the activation means when the pin 14 is removed.

As can be seen from Figure 1, a side surface of the cylinder 10 has a plurality of indicating devices in the form of LEDs 18 mounted thereon. A line of LEDs 18 extends around the entire circumference of the cylinder 10. The LEDs 18 may be individually mounted on the cylinder 10 or, alternatively, may be embedded within, or formed integral with, the outer surface of the cylinder 10.

The LEDs 18 may be chosen to transmit the colour which is associated to the material contained within the cylinder 10 of the fire extinguisher. Consequently, a person is able to tell the type of each fire extinguisher, and therefore choose the correct extinguisher to be used in the circumstances, by the colour transmitted by the LEDs 18.

The line of LEDs 18 is preferably located near the bottom of the cylinder 10, due to the fact that smoke rises and, as such, it is more likely that the LEDs 18 will be visible at low level. Moreover, the fact that the

LEDs 18 are provided low to the floor means that at least part of a pathway directed towards the fire exit is illuminated and, as such is visible in a fire situation.

It is, however, clearly the case that the LEDs 18 could be located anywhere on the outer surface of the cylinder 10 provided that they are visible from a good distance away from the cylinder 10. Moreover, the LEDs 18 may not be formed in a line, as is shown in Figure 1, the LEDs 18 may instead be individually located at various positions on the cylinder 10 surface.

In an alternative embodiment, shown in Figures 2 and 5, the LEDs 18 are mounted on a strip 20 which is, in turn, mounted on the cylinder 10. The strip 10 may be mounted on the cylinder 10 using a suitable adhesive or, alternatively, may be mounted via a male/female link mechanism, such as that which is marketed under the name VELCRO®. In this case, one member of the link mechanism is mounted on the cylinder 10 which then engages with the other link member incorporated on the strip 20 to mount the LEDs 18 on the cylinder 10.

The strip 20 may be a solar strip to provide solar power to the LEDs 18 mounted on the strip 20. Alternatively, the strip 20 may additionally hold a battery (not shown) to power the LEDs 18. In a preferred embodiment, the battery has a life of approximately one year. As such, it would be possible to synchronise the life of the battery with the annual service of the fire extinguisher on which the strip 20 and LEDs 18 are mounted in such a way that a powerless LED 18 indicates that the fire extinguisher is due for its annual service.

Figures 3 and 4 show the "working end" of the fire extinguisher. Here, an LED 22 is provided directly above the location of the pin 14 on each side of the handle 12. The LEDs 22 are incorporated on a strip 20 as described above such that the strip 20 extends across the top of the

handle and down each side towards the area of the pin 14. The strip 20 may be mounted on the fire extinguisher in a way already described. In a further embodiment (not shown) the LEDs 22 are embedded into, or formed integral with the outer surface of the cylinder 10 in the locations shown in Figure 3 and 4. A further LED (not shown) may also be located on the pin 14 itself. The location of the LEDs 22 provides illumination to the area of the pin 14, while also reflecting light to the hand of a person attempting to locate the pin 14, thus allowing the pin 14 to be found easily and quickly. In order to activate the fire extinguisher in an emergency.

Figure 6 shows a stand 24 that can be used in conjunction with such a fire extinguisher. It will be appreciated that the stand 24 is only illustrated and described in a basic form and that the invention can be applied to any type of stand suitable for holding a fire extinguisher.

The stand 24 has an LED 26 formed or mounted in a top portion. The LED 26 should be located in a position sufficiently high that the LED 26 is not obstructed from view when a fire extinguisher is placed on the stand 26 and held thereto at a connection point 28.

The LED 26 may be chosen to transmit the colour which is associated to the material contained within the cylinder 10 of the fire extinguisher held on the stand 24. The LED 24 may be embedded into, or formed integral with the top of the stand 24 or may be mounted on a strip 20 as already described.

Further LEDs 28 are mounted on, or formed within a base 30 of the stand 24. The low position of the LEDs 28 provides the same advantages associated with the low position of the LEDs 18 located on the fire extinguisher cylinder 10. Again, the LEDs 28 may be mounted on a strip 20 as already described.

Although the description refers to the indication devices being LEDs, it is clearly envisaged that they could be any form of light emitting devices.

In a further embodiment, rather than being LEDs, the indication devices provide some sort of audio signal so aid location of the fire extinguisher, or its associated stand, on which the devices are mounted. The indicators could, for example be in the form of speakers or the like. The outputted audio signal may be transmitted in response to a sensed audio signal, such as a whistle.

The above described embodiments have been given by way of example only, and the skilled reader will naturally appreciate that many variations could be made thereto without departing from the scope of the present invention.

1/2




Fig. 1




Fig. 2.




Fig. 3.




Fig. 4

2/2




Fig. 5.




Fig. 6.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.